driver has established, a pattern of exceeding the hours of service limitations of §395.3 of this part;

- (iii) The motor carrier has required or permitted a driver to fail, or the driver has failed, to accurately and completely record the driver's hours of service as required in this section; or
- (iv) The motor carrier or driver has tampered with or otherwise abused the automatic on-board recording device on any commercial motor vehicle.

[53 FR 38670, Sept. 30, 1988, as amended at 60 FR 38748, July 28, 1995]

## PART 396—INSPECTION, REPAIR, AND MAINTENANCE

Sec.

396 1 Scope.

396.3 Inspection, repair, and maintenance.

396.5 Lubrication.

Unsafe operations forbidden. 396.7

396.9 Inspection of motor vehicles in operation.

396.11 Driver vehicle inspection report(s). 396.13 Driver inspection.

396.15 Driveaway-towaway operations and inspections.

396.17 Periodic inspection.

396.19 Inspector qualifications.

396.21 Periodic inspection recordkeeping requirements.

396.23 Equivalent to periodic inspection.

396.25 Qualifications of brake inspectors.

AUTHORITY: 49 U.S.C. 31133, 31136, and 31502; 49 CFR 1.48.

SOURCE: 44 FR 38526, July 2, 1979, unless otherwise noted.

# §396.1 Scope.

General-Every motor carrier, its officers, drivers, agents, representatives, and employees directly concerned with the inspection or maintenance of motor vehicles shall comply and be conversant with the rules of this part.

[44 FR 38526, July 2, 1979, as amended at 53 FR 18058, May 19, 1988]

#### §396.3 Inspection, repair, and maintenance.

- (a) General. Every motor carrier shall systematically inspect, repair, and maintain, or cause to be systematically inspected, repaired, and maintained, all motor vehicles subject to its control.
- (1) Parts and accessories shall be in safe and proper operating condition at

all times. These include those specified in part 393 of this subchapter and any additional parts and accessories which may affect safety of operation, including but not limited to, frame and frame assemblies, suspension systems, axles and attaching parts, wheels and rims, and steering systems.

- (2) Pushout windows, emergency doors, and emergency door marking lights in buses shall be inspected at least every 90 days.
- Required records—For vehicles controlled for 30 consecutive days or more, except for a private motor carrier of passengers (nonbusiness), the motor carriers shall maintain, or cause to be maintained, the following record for each vehicle:
- (1) An identification of the vehicle including company number, if so marked, make, serial number, year, and tire size. In addition, if the motor vehicle is not owned by the motor carrier, the record shall identify the name of the person furnishing the vehicle;
- (2) A means to indicate the nature and due date of the various inspection and maintenance operations to be performed:
- (3) A record of inspection, repairs, and maintenance indicating their date and nature; and
- (4) A record of tests conducted on pushout windows, emergency doors, and emergency door marking lights on buses.
- (c) Record retention. The records required by this section shall be retained where the vehicle is either housed or maintained for a period of 1 year and for 6 months after the motor vehicle leaves the motor carrier's control.

 $[44\ FR\ 38526,\ July\ 2,\ 1979,\ as\ amended\ at\ 48\ FR\ 55868,\ Dec.\ 16,\ 1983;\ 53\ FR\ 18058,\ May\ 19,$ 1988; 59 FR 8753, Feb. 23, 1994; 59 FR 60324, Nov. 23, 19941

#### §396.5 Lubrication.

Every motor carrier shall ensure that each motor vehicle subject to its con-

- (a) Properly lubricated; and
- (b) Free of oil and grease leaks.

### § 396.7 Unsafe operations forbidden.

(a) General. A motor vehicle shall not be operated in such a condition as to